

DipSystems

Expanded Polystyrene Sheets & Blocks



DipSystems EPS briefing for Architects, Architectural Technicians, Building and Construction Specifiers

DipSystems
Insulation



Physical Address

Number 3
6th Avenue
Maraisburg, Randburg
Gauteng, South Africa

Contact details

Tel: +27 11 472 8051
Fax: +27 86 679 4271
Email: info@dipsystems.co.za
Website: www.dipsystems.co.za



DipSystems

Expanded Polystyrene Sheets & Blocks

EPS has for decades been the architect's number one choice for economy, performance and sustainability in a wide range of applications. It is the leading 21st century solution for many construction and civil engineering tasks.

DipSystems EPS insulation provides architects, engineers, craftsmen, builders and property owners with significant design and cost saving benefits:

- ✓ Cost-effective
- ✓ Durable and long lasting
- ✓ Water-repellent
- ✓ Low moisture absorption
- ✓ Diffusion-open
- ✓ Sturdy and dimensionally stable
- ✓ Environmentally friendly
- ✓ Eco-efficient
- ✓ Resistant and rot-proof
- ✓ Light weight and easy to handle
- ✓ Dust-free and easy to install
- ✓ Non-irritating to the skin

Only EPS offers a unique combination of attributes and advantages which has led to it being the leading choice for decades for architects and construction specifiers.

Expanded Polystyrene Applications

Expanded Polystyrene is ideally suited for the following applications:

- Roof, floor and wall insulation
- Sub-structures and void-fill blocks for civil engineering
- Foundation systems
- Clay Heave protection
- Bridge, rail and road widening schemes
- Underground heating system support
- Interior and exterior decorative mouldings

Suggested BOQ Specification

"DipSystems EPS sheets, density 24-36kg/m³, of (_) mm thickness and (_) mm width."

Detailed applications specific specifications will be provided on request.

Sheet and block sizes

DipSystems EPS sheets are cut according to our clients needs. Our base blocks are 6m x 1.22m in length and width respectively.



DipSystems

Expanded Polystyrene Sheets & Blocks

Expanded Polystyrene Attributes

Lightweight

EPS offers an exceptionally lightweight solution to so many applications in construction. This is not surprising when you consider that, as a result of advanced manufacturing technologies, EPS is effectively 98% air captured within a 2% cellular matrix.

The advantages in on-site handling and transportation bring significant economic benefits whilst considerably reducing health and safety risks associated with the lifting of heavier materials. It is therefore an excellent substitute for infill materials and ballast where it also brings load and fill times down in time-critical build projects.

High Strength and Structural Stability

In spite of its light weight, the unique matrix structure of EPS brings the benefits of exceptional compressive strength and block-rigidity. This means it is ideal for use in many construction and civil engineering applications, particularly as a structural base infill, for example in road, railway and bridge infrastructures.

Strength tests performed on EPS which was first placed in the ground almost 30 years ago show that it is just as strong today – the tested strength routinely exceeding the original minimum design strength of 100kPa. EPS bridge foundations, which have been subject to many years of sustained loading, show ‘creep’ deformation of less than 1.3% - only half as much as had been theoretically predicted. Most importantly, EPS stability does not deteriorate with age.

Economy

EPS is a well-established material for the construction industry and offers a proven and economic solution which helps specifiers maintain build costs and insulation budgets. Far from incurring a cost premium, the new-build cost of insulating a building with EPS, rather than polyurethane, polyisocyanurate or mineral wool, is typically 20% less.

Floor construction with EPS requires only one waterproof membrane to be installed, not the two needed for mineral wool or PU foam – saving on both material and labour. And for a given insulation performance, EPS itself costs less than these competing materials.

Insulation

In the construction sector, EPS has a long established reputation for its exceptionally high insulation qualities. EPS is the perfect choice for use in under-floor, between-floor, walling and roofing applications where it is able to give a constant insulation value across the full service life of the building.

Thermal conductivity testing of EPS shows that its insulation efficiency at 0.0345W/m.K. Higher values can be achieved using Neopor which is graphite-enhanced EPS.



DipSystems

Expanded Polystyrene Sheets & Blocks

Design Versatility

Ease of cutting or moulding allows the factory production or on-site preparation of complex shapes to match the most demanding architectural and design requirements – usually without the need for specialist cutting tools or skills. This means the breathing masks, goggles and protective gloves needed for working with mineral wool and other materials are not required with EPS.

Accredited Performance

EPS has a long and proven track record and has been tested to some of the world's most demanding performance standards. EPS has BBA Approval, BRE Certification and many wider industry accreditations.

Its light weight, high compressive and impact strength, insulation, safety and eco-credentials combine to make it the preferred option for so many architectural and construction applications.

Resistance to Water Ingress

After almost 30 years in the ground, samples of EPS retrieved from locations as little as 200mm above the groundwater level all have less than 1% water content by volume, whilst blocks which are periodically entirely submerged show less than 4% water content – performance notably superior to other foamed plastic materials.

Safety in installation and use

EPS is non-toxic, chemically inert, non-irritant and rot-proof. Fungi and bacteria cannot grow on EPS and it is insoluble and non-hygroscopic.

EPS is also rodent-proof and offers no nutrient attraction to vermin. Nor is it affected by water, thus ensuring that moisture contact will not lead to deterioration of the product or its performance.

In fact, the reinstatement of flood- damaged buildings is a much quicker, more practical and less costly procedure if building structures feature non-water-absorbing insulation material -

waterlogged open-cell foams and mineral fibres are very vulnerable to flood damage, are very hard to dry out and may never recover their insulation performance.

Cement, lime, gypsum, anhydrite and mortar modified by plastics dispersions have no effect on EPS, so it can confidently be used in conjunction with all conventional types of mortar, plaster and concrete encountered in building construction. All of this makes it entirely safe in use across all of its construction applications including subterranean and marine environments.

Sustainability Credentials

At every stage of its life cycle, from production to recovery or recycling, EPS offers exceptional eco-credentials and is therefore ideally suited to the new generation of eco-friendly building projects. All manufacturing processes comply with current environmental regulation. EPS uses no greenhouse gas producing materials. It is chemically and environmentally non-aggressive and it can be – and is – easily recycled into long-life products through an expanding nationwide network of collection points.



DipSystems

Expanded Polystyrene Sheets & Blocks

Expanded Polystyrene Composition

Put simply, EPS is 98% air and 2% plastic. It uses, as its base material, styrene monomer. The monomer is a by-product of petroleum and naphtha produced during oil refining which provides a ready and continuous source. Styrene also occurs naturally in many foods such as strawberries, coffee beans, beer and wine.

Polystyrene is produced when the styrene monomer is polymerised into long chains. A gas called pentane is used as a non-CFC expansion agent to blow polystyrene into its final lightweight, expanded cellular form. During the production process, the pentane is quickly broken down into carbon dioxide and water. Pentane has low volatility. For example, it is found in the digestive systems of animals and created when vegetable matter decomposes in a process called anaerobic composting.

On the basis of current EU testing and classification regimes, styrene monomer is non-toxic in all normal usage and is not classified in terms of carcinogenicity or mutagenicity.

Pentane has no potential to harm the ozone layer unlike CFCs or HCFCs.

Expanded Polystyrene Processing

EPS has been made for more than half a century and EPS manufacturers comply with all current regulatory and legislative requirements.

The processes include a combination of heat and pressure utilising clean technologies and minimising energy inputs and water usage through closed loop energy recycling. For all of these reasons, EPS manufacture is a highly efficient process.

No solid waste is created and process waste and off-cuts are reintroduced to the production batch immediately. Atmospheric and land/water emissions are strictly controlled, resulting in minimal localised impacts.



DipSystems

Expanded Polystyrene Sheets & Blocks

Expandable Polystyrene Performance

- ✓ EPS has been established in use for more than 50 years.
- ✓ EPS is one of the 'elite' groups of construction materials with the lowest environmental impacts.
- ✓ EPS is the closest of any modern building material to fulfilling the 60yr life target.
- ✓ EPS boasts eco points projected over a 60yr life of only 0.043. This acts as a clear assurance to specifiers of the eco-credentials of EPS and its significant benefits when it comes to environmental impact assessment.
- ✓ EPS is non-hygroscopic, non-irritant and rot-proof. It does not deteriorate over time and requires no special storage conditions.
- ✓ EPS provides a constant insulation value across the full life of a building – offering thermal conductivity as low as 0.038 W/m.K.
- ✓ EPS is dimensionally stable to within 0.2% at 230C and 50% RH
- ✓ Where there is no mechanical load, EPS can be exposed to temperatures of up to 900C.
- ✓ Hot bitumen is a particularly suitable adhesive for roofing and cold store applications – the very short term exposure to temperatures of over 1000C has practically no effect.
- ✓ There are no lower temperature limits for EPS unless structural circumstances indicate that a volume change would be critical.
- ✓ Unlike fibrous materials, EPS will not settle over time.
- ✓ EPS is widely used throughout the construction industry in a flame-retardant grade where its trusted performance has been established over decades in use.
- ✓ EPS should be specified for installation in a protected/enclosed environment such as under concrete screed, behind plasterboard, in building cavities and underground.
- ✓ EPS is combustible, but the flame-spread with flame-retardant EPS is markedly reduced. EPS will extinguish on removal of the igniting flame.
- ✓ The fire behaviour of naked EPS insulation material is not relevant. The material is generally covered by other material which determines the fire behaviour. The insulation material is only affected by fire after the covering material fails and by this time the building or the compartment cannot be saved from total loss.
- ✓ EPS is well proven in decades of use in civil engineering applications where it has been subjected to millions of loading cycles, for example, in road and railway structures.
- ✓ EPS has long been regarded as a high-performance, value-for-money material. The established, well-invested and highly efficient manufacturing processes help manufacturers to maintain competitive pricing policies when compared with other, less effective and higher installed-cost alternatives. Together with its outstanding environmental attributes, this makes EPS the best choice for sustainable building projects.



DipSystems

Expanded Polystyrene Sheets & Blocks

Environmental impacts

Production Impacts

- ✓ EPS manufacturers use advanced 'clean technologies' and operate to strict environmental management procedures.
- ✓ EPS is 98% air. It uses no CFCs or HCFCs in manufacture and all emissions are controlled strictly within environmental regulatory frameworks.
- ✓ EPS brings considerable energy and resource- saving benefits. Using less than 0.1% of global oil as a feed- stock, it can save up to 200 times its own resource in thermal energy saving.
- ✓ All energy, heat and water in-puts at manufacture are strictly monitored and maximum use is made of re-use and recycling on a closed loop basis wherever possible.
- ✓ EPS manufacturing units do not produce residual solid waste from the production process.
- ✓ All process waste, off-cuts etc, is recycled into the production process.
- ✓ The inherent light weight of EPS makes it the lightest of all construction materials in common use - thus helping minimise environmental impacts and costs associated with the movement of heavier materials.
- ✓ Eco-balances and life-cycle analyses demonstrate that EPS has exceptional merits as a construction material. For example, it has a Zero Ozone Depletion Potential and a low Global Warming Potential.

Environmental Advantages in Use

- ✓ EPS has outstanding thermal insulation qualities which make it a first choice material for many construction applications. EPS reduces CO2 emissions by up to 50% - making sure it more than offsets its small carbon footprint - giving maximum return for minimal resource.
- ✓ Heating and cooling of buildings accounts for a vast amount of energy consumption. By acting as a highly efficient thermal insulator, EPS can also make a significant contribution to reducing fossil fuel for these purposes. In turn, this helps reduce SO2 and SO3 emissions – a major cause of acid rain.
- ✓ EPS has extremely low moisture absorption and will never rot. Together with its outstanding ageing performance and chemical resistance, it offers exceptional durability which, in turn, overcomes the need for replacement which would mean resource wastage.

Post-Use Environmental Credentials

- ✓ EPS is recyclable at many stages of its life cycle. During production, all manufacturing waste can be fully reprocessed by milling or granulating into pellets and adding to the production mix without any detriment to the quality of the finished EPS product.
- ✓ The integrity and performance of EPS can be expected to last at least the full lifetime of the building in which it is used. At the end of its useful life, however, the fact that EPS does not degrade or deteriorate throughout its life means that it is ideal for recovery and recycling.

